

Collano Hardener HR 910

Crosslinking agent for dispersion adhesives

Characteristics

Base

Emulsifiable, aliphatic isocyanate

Colour

Colorless

Density

1.14 g/cm³

Solids content

100%

Fluidity

Flowing

Viscosity (Brookfield)

1'400 mPa·s

Form

Liquid

Storage

12 months in unopened original packaging at 15–25 °C

Application area and materials

For the improvement of mechanical, thermal and chemical resistance of dispersion adhesives and coatings.

Application

Admix Collano Hardener HR 910 according to the information on the technical data sheet of the corresponding product and process within pot life. The viscosity of crosslinked adhesive increases after the pot life and the product can not be processed any more. Applicator and equipment can be cleaned with water. By adding Collano HP 3100 to the water, the cleaning process can be improved.

Additional details

The formulated adhesive should not be stored into sealed packaging. The packaging can be damaged through the carbon dioxide gas generated.

Safety

Follow the instructions on the Safety Data Sheet.

Packaging

Alu bottles 50 g
Plastic bottles 500 g

Guarantee

We guarantee the consistency and faultless quality of this product, manufactured in accordance with ISO quality standards, which has been developed on the basis of our long standing experience with the recommended applications under the specified conditions. Material, processing, and application conditions may significantly influence product properties. Pre-application tests by the user are therefore essential. For non-specified applications or deviations in application conditions, we recommend that Collano's technical support service be consulted first. Collano's general sales and delivery terms and conditions shall apply.

Collano AG

6203 Sempach Station · Schweiz · T +41 41 469 92 75
info@collano.com · www.collano.com